

IMAGE FORMING APPARATUS

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates in general to an image forming apparatus adopting an electrostatic system, an electrophotographic recording system, or the like. In particular, the present invention relates to an image forming apparatus for forming an
10 image such as a dot pattern other than a normal image on an image bearing body in order to prevent an image defect when a developer image on an image bearing body is transferred onto a transferring medium such as an intermediate transferring body or a
15 transferring material.

Related Background Art

 Heretofore, there has been used an image forming apparatus having a plurality of image forming units as recording units in each of which a laser
20 beam or a light emitted from a light emitting element such as an LED which is light-modulated in accordance with external information is applied to an image bearing body such as a photosensitive drum having a surface charged with electricity corresponding to a
25 predetermined potential to change the potential of a portion irradiated with the light to thereby form an electrostatic latent image, the electrostatic latent

image on the photosensitive drum is developed, and a developer image (toner image) is transferred onto a transferring medium such as a transferring material or an intermediate transferring body conveyed by a transferring material conveying body. Regarding such image forming apparatus, there has been proposed an image forming apparatus capable of forming a color image by utilizing a method in which: respective image forming units form images having different colors, and the images are transferred onto the transferring materials one on the other while transferring materials are successively conveyed to the recording units; or after the images are transferred onto an intermediate transferring body one on the other, the images are collectively transferred onto a transferring material.

Here, a primary transfer system in which an image is transferred from a photosensitive drum to a belt-like intermediate transferring body (intermediate transferring belt) will be described as an example. In an image forming apparatus of this sort, it is conceivable that in particular, for the purpose of enhancing a primary transfer latitude, a primary transfer current is optimally set. However, when the primary transfer current is low, transfer deficiency is caused, while retransfer is caused when the primary transfer current is high.

For this reason, for the purpose of realizing the enhancement of the primary transfer latitude, a method including providing a difference in peripheral speed between each of the photosensitive drums and the intermediate transfer belt, is suitably implemented. This provision of the difference in peripheral speed results in that in particular, a central portion of a fine line of a secondary color is not omitted to realize enhancement of the transfer latitude. However, a frictional force is usually generated between each of the photosensitive drums and the intermediate transferring belt due to the difference in peripheral speed.

A coefficient of friction is changed between a case where there is developer (toner) between each of the photosensitive drums and the intermediate transferring belt and a case where there is no developer between each of the photosensitive drums and the intermediate transferring belt due to the frictional force generated between each of the photosensitive drums and the intermediate transferring belt, so that a rotational speed of each of the photosensitive drums fluctuates. This results in that image exposure to the photosensitive drums is blurred and thus an image streak is generated.

This phenomenon also occurs in a transfer system for transferring a toner image onto a

transferring material conveyed from the
photosensitive drums to the transferring material
conveying body. In this case, the transferring
material conveying body and the intermediate
5 transferring body are collectively referred to as a
transfer/movement unit.

A problem is described in Japanese Patent
Application Laid-open No. H11-52758 (or US Patent No.
6,091,922) that with a construction in which no
10 difference in peripheral speed is provided between an
image bearing body and a transfer/movement unit, a
non-intentional speed difference is generated due to
decentering or the like of a drive roller, and as a
result, color drift is generated. Further, in
15 Japanese Patent Application Laid-open No. H11-52758
(or US 6,091,922), there is described a construction
in order to solve this problem. That is, dot toner
images are dispersedly formed in the form of
predetermined minute dots so as to overlap a normal
20 image, so that an image is more stably formed to
allow an image of high quality to be printed.

However, in many cases, such a 'dot pattern is
formed so as to overlap a toner image as a normal
image, which is intentionally formed by a user based
25 on external information. Thus, there arises a first
problem in that if each dot toner image is formed in
a state of laser full lighting using the above-

mentioned image forming apparatus when a
predetermined dot pattern is formed, even when a dot
toner image is formed with yellow toner so as to be
made inconspicuous, the dot toner image formed with
5 yellow toner becomes conspicuous in a portion (white
background portion) to which no toner is transferred
in the toner image formed on the basis of the
external information.

Further, there arises a second problem in that
10 when conversely, a dot pattern is formed not in a
state of the laser full lighting, but in a half tone
state, since a color of the dot pattern appears to be
missing in a set-solid portion in the toner image
formed on the basis of the external information, a
15 normal image appears to be rough to reduce quality of
image.

Moreover, generation of an image streak due to
a change in frictional force is not limited to only a
case of the formation of a color image as a normal
20 image. Thus, for example, in a case where an image
of black (K) monochrome is formed as a normal image
by a color copying machine, or even in a case where
an image is formed by a monochrome copying machine, a
light and shade image streaks appear due to a change
25 in frictional force. For this reason, in formation
of an image of black monochrome as well as in
formation of an image by the monochrome copying

machine, there is a need to form a dot pattern with black toner. However, when a dot pattern is formed with black toner, for both the above-mentioned first and second problems, the disadvantages such as the
5 conspicuousness and the roughness of the dot pattern are emphasized as compared with a case where a dot pattern is formed with yellow toner. As a result, the reduction of image quality becomes a serious problem.

10

SUMMARY OF THE INVENTION

In the light of the foregoing, it is, therefore, an object of the present invention to provide an image forming apparatus which is capable of
15 suppressing conspicuousness of a dot image formed so as to overlap a normal image, and roughness resulting from the conspicuousness to satisfactorily form an image in an image forming apparatus for forming a dot image other than a normal image.

20 In order to attain the above-mentioned object, a preferable image forming apparatus according to the present invention includes:

- a movable image bearing body;
- image forming means for forming a developer
25 image on the image bearing body;
- transferring means for transferring the developer image formed on the image bearing body onto

a moving transferring medium; and

control means for controlling the image forming means to form a predetermined image composed of dot images with a predetermined density prior to

5 formation of a normal image,

wherein the control means controls the image forming means so as to:

form a composite image from the normal image and the predetermined image in an area where the
10 normal image is to be formed; and

form the dot images in a dot area having the normal image and the predetermined image overlapped with each other, with a density determined on the basis of a relationship between a density of the
15 normal image and the predetermined density in the dot area.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a flow chart showing a method
20 including determining density of a dot developer image according to the present invention;

FIG. 2 is a timing chart showing an example of a timing at which a dot dispersion image is formed according to the present invention;

25 FIG. 3 is a front view showing an example of a dot dispersion image and a normal image area according to the present invention;

FIG. 4 is a block diagram showing an example of a control circuit for determining density of a dot developer image according to the present invention;

FIG. 5 is a block diagram showing an example of
5 a control circuit for forming a dot dispersion image according to the present invention;

FIG. 6 is a timing chart useful in explaining an example of a method including forming a dot dispersion image according to the present invention;

10 FIG. 7 is a diagram useful in explaining an example of a method including forming a dot dispersion image according to the present invention;

FIG. 8 is a block diagram showing another example of a control circuit for determining density
15 of a dot developer image according to the present invention;

FIGS. 9A and 9B are respectively diagrams of PWM tables each showing a relationship between a pulse width and density data used in another example
20 of a control circuit for determining density of a dot developer image according to the present invention;

FIG. 10 is a schematic constructional view showing an example of an image forming apparatus according to the present invention;

25 FIG. 11 is a schematic constructional view showing an example of a mechanism for detecting color drift; and

FIG. 12 is a cross sectional view showing an example of another image forming apparatus according to the present invention.

5 DESCRIPTION OF THE PREFERRED EMBODIMENTS

An image forming apparatus according to the present invention will hereinafter be described in more detail with reference to the accompanying drawings.

10 First Embodiment

An image forming apparatus according to a first embodiment of the present invention will hereinbelow be described in more detail with reference to the accompanying drawings.

15 FIG. 10 is a cross sectional view of a main portion of an image forming apparatus in which the present invention is implemented. The image forming apparatus of this embodiment is described as a color image outputting apparatus 1 in which an
20 electrophotographic system is adopted. In formation of a normal image, an image of an original as external information is read out in an optical system 1R. In an image output unit 1P, the image obtained from the external information from the optical system
25 1R is formed on a transferring material P. Moreover, a plurality of image forming units 10 for each of which the present invention is judged to be

especially effective are arranged in parallel in the image output unit 1P. In addition, an intermediate transfer system is adopted.

The image output unit 1P is roughly composed of
5 an image forming unit 10 in which four stations 10a, 10b, 10c, and 10d having the same construction are provided in parallel, a sheet feeding unit 20, an intermediate transferring unit 30, a fixing unit 40, and a control unit 80 (refer to FIG. 11).

10 Moreover, the individual units will now be described in detail. The image forming unit 10 has a construction as will be described below. In the stations 10a, 10b, 10c, and 10d, photosensitive drums 11a, 11b, 11c, and 11d as image bearing bodies are
15 rotatably supported with their centers and adapted to be driven and rotated in a direction indicated by arrows, respectively. Primary chargers 12a, 12b, 12c, and 12d, exposing units 13a, 13b, 13c, and 13d of an optical system serving as an exposure unit, folding
20 mirrors 16a, 16b, 16c, and 16d, and developing units 14a, 14b, 14c, and 14d are arranged so as to confront outer peripheral surfaces of the photosensitive drums 11a, 11b, 11c, and 11d along the direction of rotation, respectively.

25 In the primary chargers 12a to 12d, surfaces of the photosensitive drums 11a to 11d are given charges having a uniform charge amount. Next, in the

exposing units 13a to 13d, light beams such as laser beams which are modulated in accordance with a recording image signal are applied onto the photosensitive drums 11a to 11d through the folding
5 mirrors 16a to 16d to expose the photosensitive drums 11a to 11d to thereby form electrostatic latent images on the photosensitive drums 11a to 11d, respectively.

Moreover, the above-mentioned electrostatic
10 latent images are visualized by the developing units 14d, 14c, 14b, and 14a in which developers of four colors composed of yellow, cyan, magenta, and black (hereinafter referred to as "toner" for short when applicable) are accommodated, respectively. Then,
15 developer images (toner images) as visible images obtained through visualizing process are transferred onto an intermediate transferring belt 31 as an intermediate transferring body serving as a transferring medium in primary transferring portions
20 Ta, Tb, Tc, and Td, respectively.

On downstream sides where the photosensitive drums 11d to 11a are rotated to pass through the primary transferring portions Td to Ta, the residual toner which is not transferred onto the intermediate
25 transferring belt 31, but is left on the photosensitive drums 11d to 11a is removed by cleaning units 15d, 15c, 15b, and 15a to clean the

surfaces of the photosensitive drums 11d to 11a, respectively.

The images are successively formed with the four kinds of toners through the above-mentioned
5 process.

The sheet feeding unit 20 is composed of cassettes 21a and 21b for accommodating therein transferring materials P, a manual feed tray 27, pick-up rollers 22a, 22b, and 26 for feeding the
10 transferring materials P sheet by sheet from the cassettes 21a and 21b or from the manual feed tray 27, sheet feeding roller pairs 23 and a sheet feeding guide 24 for conveying the transferring materials fed from the pick-up roller 22a, 22b, or 26 to
15 registration rollers 25a and 25b, and the registration rollers 25a and 25b for feeding the transferring materials P to a secondary transferring area Te at the same timing as formation of images in the image forming unit.

20 The intermediate transferring unit 30 will hereinbelow be described in detail. The intermediate transferring belt 31 serving as the transferring medium is wound around a drive roller 32 for transmitting a driving force to the intermediate
25 transferring belt 31, a driven roller 33 for being driven so as to follow the rotation of the intermediate transferring belt 31, and a secondary

transferring confronting roller 34 provided so as to face the secondary transferring area Te through the intermediate transferring belt 31. The drive roller 32, the driven roller 33 and the secondary
5 transferring confronting roller 34 are winding rollers. A primary transferring plane is defined between the drive roller 32 and the driven roller 33 of these rollers.

The drive roller 32 is constructed by coating a
10 surface of a metallic roller with rubber (urethane or chloroprene) with several millimeters thickness in order to prevent the drive roller 32 from slipping on the intermediate transferring belt 31. The drive roller 32 is driven and rotated in a direction
15 indicated by an arrow by a pulse motor (not shown).

The primary transferring plane confronts the image forming units 10a to 10d. In a space defined between the primary transferring plane and the image forming units 10a to 10d, the photosensitive drums
20 11a to 11d confront a primary transferring surface T of the intermediate transferring belt 31. Thus, the primary transferring portions Ta to Td are located on the primary transferring surface T.

In the primary transferring portions Ta to Td
25 which each of the photosensitive drums 11a to 11d, and the intermediate transferring belt 31 confront, chargers 35a, 35b, 35c, and 35d for primary transfer

are arranged so as to contact a rear face of the intermediate transferring belt 31. In addition, a secondary transferring roller 36 is arranged so as to confront the secondary transferring confronting roller 34. Then, a secondary transferring area Te is formed by a nip portion defined on the intermediate transferring belt 31. The secondary transferring roller 36 is pressed against the intermediate transferring belt 31 under a suitable pressure.

10 In addition, a cleaning blade 51 for cleaning an image formation surface of the intermediate transferring belt 31, and a waste toner box 52 for accommodating therein waste toner are provided on a downstream side of the secondary transferring area Te
15 on the intermediate transferring belt 31.

The fixing unit 40 is composed of a fixing roller 41a including a heat source such as a halogen heater in its inside and a roller 41b pressed by the fixing roller 41a (the roller 41b may also include a
20 heat source in some cases), a guide 43 for guiding the transferring material P to a nip portion of the above-mentioned roller pair 41, an inner sheet discharging roller 44 and an outer sheet discharging roller 45 for further guiding the transferring
25 material P discharged through the roller pair 41 to the outside of the image forming apparatus, and the like.

The control unit 80 is composed of a CPU (not shown) for controlling the operations of the mechanisms within the above-mentioned units, a control substrate (not shown), a motor drive
5 substrate (not shown) and the like. Upon issue of an image formation operation start signal from the control unit 80, the transferring materials P are started to be fed from a sheet feeding stage selected depending on a selected paper size and the like.

10 Next, a description will hereinbelow be given on the basis of the operation of the image forming apparatus 1.

Upon issue of the image formation operation start signal from the control unit 80, first of all,
15 the transferring materials P are fed sheet by sheet from the cassette 21a or 21b, or the manual feed tray 27 by the pick-up roller 22a or 22b, or 26. Then, the transferring material P is guided through the sheet feeding guide 24 by the corresponding one of
20 the sheet feeding roller pairs 23 to be conveyed to the registration rollers 25a and 25b. At this time, the registration rollers 25a and 25b are stopped, and hence a leading end of the transferring material P is brought into contact with the nip portion of the
25 registration rollers 25a and 25b. Thereafter, the registration rollers 25a and 25b start to be rotated at in accordance with the timing when the image

forming units 10a to 10d start to form images,
respectively. The timing of the rotation of the
registration rollers 25a and 25b is set such that the
transferring material P, and the developer images
5 (toner images) primarily transferred onto the
intermediate transferring belt 31 by the image
forming unit 10 just meet in the secondary
transferring area Te.

On the other hand, in the image forming unit 10,
10 upon issue of the image formation operation start
signal from the control unit 80, the toner image
formed on the photosensitive drum 11d located in the
most upstream side in a rotating direction of the
intermediate transferring belt 31 is primarily
15 transferred onto the intermediate transferring belt
31 in the primary transferring area Td by the charger
35d for primary transfer to which a high voltage is
applied through the above-mentioned process.

The primarily transferred toner image is
20 carried up to the next primary transferring area Tc.
In the primary transferring area Tc, the image
formation is carried out after a time delay by a
period of time required for the toner image to be
carried to the primary transferring area Tc, and the
25 next image is transferred in a state where the
registration (image position) is adjusted onto the
first image. The same process is repeatedly carried

out for the primary transferring areas Ta and Tb of other colors, and finally, the toner images of the four colors are primarily transferred onto the intermediate transferring belt 31 in an overlapped
5 manner.

Thereafter, when the transferring material P enters the secondary transferring area Te and comes into contact with the intermediate transferring belt 31, a high voltage is applied to the secondary
10 transferring roller 36 at the same timing as the passing of the transferring material P. Then, overlapped toner images of the four colors formed on the intermediate transferring belt 31 through the above-mentioned process are collectively transferred
15 onto the surface of the transferring material P. Thereafter, the transferring material P is accurately guided to the nip portion of the fixing roller pair 41 by a conveyance guide 43. Then, the toner images are fixed to the surface of the transferring material
20 P with the heat of the fixing roller pair 41 and the pressure at the nip portion. Thereafter, the resultant sheet is conveyed by the inner and outer sheet discharging roller pairs 44 and 45 to be discharged to the outside 48 of the image forming
25 apparatus 1.

A registration sensor 60 for detecting misregistration is provided for the purpose of

correcting deviation of registration of the color
images formed on the respective photosensitive drums
11a to 11d, i.e., the color drift (misregistration)
due to the mechanical mounting error appearing among
5 the photosensitive drums 11a to 11d, the optical path
length errors and the optical path changes in the
laser beams generated through the respective exposing
units 13a to 13d, the warpage caused by the
environmental temperature of the LED, and the like.

10 The registration sensor 60 is located in a position
on the transferring area on the downstream side of
the whole image forming unit 10 and before the drive
roller 32 that folds the intermediate transferring
belt 31. When color drift occurs due to a change in
15 rotational speed of each of the photosensitive drums
11a to 11d resulting from a difference in speed
between the intermediate transferring belt 31 and
each of the photosensitive drums 11a to 11d, the
color drift is detected by the registration sensor 60.

20 FIG. 11 is a schematic view in the vicinity of
the registration sensor 60 (including an LED as a
light emitting body, and a photodiode as a light
receiving body) as a color drift detecting unit for
detecting patterns for registration correction
25 (images for color drift detection).

The pattern images for registration correction
(images for color drift detection) which are formed

from the photosensitive drums 11a to 11d onto the intermediate transferring belt 31 in accordance with a signal outputted from a unit 81 for generating patterns for registration correction in the control unit 80 are read by the registration sensor (detection unit) 60 as a color drift detecting unit composed of the light emitting element and the light receiving element to detect the misregistration on the photosensitive drums 11a to 11d corresponding to the four colors. Then, an image signal to be recorded is electrically corrected, or the folding mirrors 16a to 16d provided in the optical paths of the laser beams are driven by a color drift correcting unit included in the control unit 80 to thereby correct a change in the optical path length or a change in optical path.

The intermediate transferring belt 31 is an endless belt made of an elastic body containing rubber, elastomer, or the like as a raw material, and has Young's modulus of equal to or larger than 10^7 Pa in a circumferential direction. A thickness of the intermediate transferring belt 31 is desirably in the range of 0.3 to 3.0 mm from a viewpoint of ensuring thickness accuracy and strength and of realizing a flexible rotary motion. Moreover, a resistivity of the intermediate transferring belt 31 is adjusted to a desired value (a volume resistivity is desirably

equal to or lower than 10^{11} Ωcm) by adding electroconductive agent such as metallic powder (e.g., carbon powder).

In addition, in this embodiment, for the purpose of increasing the primary transferring latitude, a peripheral speed difference is set such that a travel speed of the intermediate transferring belt 31 is higher than a rotational speed of each of the photosensitive drums 11d to 11a by several percentages.

In the image forming apparatus in which the peripheral speed difference is set between each of the image bearing bodies and the intermediate transferring body, before a normal image is formed on the basis of external information obtained by reading an original with the optical system 1R through the above-mentioned process, a predetermined image is formed onto the intermediate transferring belt.

Normally, in a case where there is a peripheral speed difference between each of the photosensitive drums 11a to 11d and the intermediate transferring belt 31, a frictional force is generated between each of the photosensitive drums 11a to 11d and the intermediate transferring belt 31. Then, the frictional force is changed between a case where there is toner between each of the photosensitive drums 11a to 11d and the intermediate transferring

belt 31 and a case where there is no toner between each of the photosensitive drums 11a to 11d and the intermediate transferring belt 31. As a result, the rotational speed of each of the photosensitive drums 11a to 11d fluctuates so that the image exposure to each of the photosensitive drums 11a to 11d is blurred to generate an image streak in an image leading end portion.

The generation of the image streak in the image leading end portion means that the rotational speed of each of the photosensitive drums 11a to 11d fluctuates in a position where image transfer begins when an area is changed from a non-image area to an image area (i.e., a state is abruptly changed from a state where there is no toner to a state where there is toner) in the transferring portions Ta to Td defined between the photosensitive drums 11a to 11d and the transferring belt 31 to thereby readily blur the image.

Then, before the toner images formed on the photosensitive drums 11a to 11d are transferred, a predetermined image is previously formed between the transferring belt 31 and each of the photosensitive drums 11a to 11d, respectively, in order to avoid a situation where from a time point when a sheet area (transferring material area) has entered each of the transferring portions Ta to Td, a state is abruptly

changed from a state where there is no toner to a state where there is toner since entrance into the image areas is made because the toner is present between the transferring belt 31 and each of the
5 photosensitive drums 11a to 11d. Accordingly, it is possible to relax the fluctuation in the rotational speed of each of the photosensitive drums 11a to 11d. As a result, the stable image formation is carried out.

10 In the present invention, the predetermined image is formed in the form of a dot dispersion image (hereinafter referred to as "a dot pattern" when applicable) in which toner images (hereinafter referred to as "dot developer images each having a
15 minute area in units of one or plurality of dots (dot toner images)" when applicable) such that no dot is marked in a fixed main scan position. This is because if a dot is usually dotted in the fixed main scan position, then there is encountered a problem
20 such that longitudinal streak dirt is generated on the secondary transferring roller 36, the toner collects in a specific position of the cleaning blade 51, or the dot toner images transferred onto the transferring material P are conspicuous.

25 Note that, in this case, a direction along which the drums are scanned with the respective laser beams, i.e., a direction crossing a travel direction

of the intermediate transferring belt 31 is referred to as a main scan direction, and a direction along which the photosensitive drums 11a to 11d, and the transferring belt 31 are moved is referred to as a
5 sub-scan direction.

In order to prevent a change in coefficient of friction between the intermediate transferring belt 31 and each of the photosensitive drums 11a to 11d which is generated depending on presence or absence
10 of the toner between the intermediate transferring belt 31 and each of the photosensitive drums 11a to 11d, it is necessary to form the dot pattern before the formation of the normal image. However, in this embodiment, the dot pattern is continuously formed
15 from a time point before the formation of the normal image to a time point at completion of the formation of the normal image.

FIG. 2 is a timing chart regarding formation of the dot pattern in this embodiment. In the figure,
20 "a sheet area signal" means a sheet area (transferring material area) signal in the sub-scan direction corresponding to a sheet size of the transferring material P, and "an image formation timing signal" means a timing signal with which the
25 formation of the normal image is actually started. Also, "a dot pattern area signal" means an image area signal with which the dot pattern of the present

invention is formed on the intermediate transferring belt 31. Then, as shown in the figure, the formation of the predetermined dot pattern is started before the formation of the normal image.

5 Moreover, in this embodiment, when N sheets of transferring materials P are continuously printed, the dot pattern is continuously formed for a period of time ranging from the image area start timing for the first sheet to the image area end timing for the
10 N-th sheet. Also, a composite image is formed from the dot pattern and the normal print image for a period of time for the normal print image area.

FIG. 3 shows the normal image area and the dot pattern area which are formed at such timings on the
15 intermediate transferring belt 31.

The whole area of a sheet area (transferring material area) including an area which is indicated by slant lines and which is located outside the normal image area shows a dot pattern area, and an
20 image of the dot pattern is an image drawn with slant lines in the figure.

An area drawn with dots inside the dot pattern area shows a normal image area, and also shows an area where an image is formed in accordance with a
25 sub-scan directional image formation timing signal. Here, the dot pattern is formed so as to overlap the normal image in the normal image area.

This results in that a gap disappears between the normal image area and the dot pattern area on the upstream side in the travel direction of the intermediate transferring belt 31 having the normal
5 image formed therein. Hence, it is possible to avoid a fluctuation in a coefficient of friction due to a change of a position from a portion having no toner in each of the transferring nips Ta to Td to a portion having the toner.

10 With respect to the dot pattern in the immediately upstream portion of the normal image area in the travel direction of the intermediate transferring belt 31, it is preferable that as described above, there is no gap between the normal
15 image area and the dot pattern area. However, even when the dot toner images are formed at a timing other than the timing shown in FIG. 2, if the dot toner images are present within the transferring material area, then the toner is present between the
20 intermediate transferring belt 31 and each of the photosensitive drums 11a to 11d before transferring the normal print image. Hence, it is possible to reduce a change in coefficient of friction generated between the intermediate transferring belt 31 and
25 each of the photosensitive drums 11a to 11d. In addition, a portion of the dot pattern which is formed within the transferring material area other

than the normal image formation area is adapted not to be transferred onto the transferring material P by adjusting the operation timing of the secondary transferring roller 36.

5 In addition, in this embodiment, in the station 10d on the most upstream side of the primary transferring plane T, yellow toner is accommodated in the developing unit 14b and thus the station 10d is assigned a Y station for forming a yellow toner image.

10 Then, in the Y station, minute dot toner images are formed so as to overlap the image of yellow (Y). Other stations 10a, 10b and 10c are assigned K, C and M stations, respectively, and black (K) toner, cyan (C) toner, and magenta (M) toner are accommodated in

15 the developing units 14a, 14b and 14c, respectively. Then, in these K, C and M stations, the toner images of black, cyan and magenta are formed, respectively. Thus, there is an advantage such that the dot toner images are added to the image in the most upstream

20 station, whereby the dot toner images function to relax a fluctuation of the frictional force in the temporary transferring in all the downstream stations. In addition, if the dots concerned are yellow dots, then it is advantageous because the yellow dots are

25 hardly conspicuous after being transferred onto the transferring material P as compared with M, C, and K dots.

A method for forming a dot pattern will hereinbelow be described.

The image data to be inputted to the exposing unit 13d is generated in accordance with a block
5 diagram shown in FIG. 4.

The external information for forming the normal image inputted from a host PC 101 or a reader (image reading unit) 102 within the control unit 80 is processed in an image processing unit 103 to be
10 outputted in the form of a normal image signal (a') with which a laser unit 105 acting on the exposing units 13a to 13d is driven. In addition, in a dot pattern forming unit 106, a dot pattern signal (b) with which the dot pattern having minute dot toner
15 images dispersed therein is formed is generated.

While a processing in a density discriminating circuit 104 will be described in detail later, a normal image density value A based on image density information (a) contained in the normal image signal
20 (a') is directly sent, or a predetermined density value B defined for the dot pattern is sent to a PWM circuit 107 depending on whether a logical value of the dot pattern signal (b) is 1 or 0. Then, in the PWM circuit 107, the density data is converted into a
25 pulse width signal in accordance with a PWM table for generation of a signal with a pulse width corresponding to an image density signal as shown in

FIG. 9A to be sent to the laser unit 105. Then, the toner image formed on the photosensitive drum 11d becomes an overlapped image in which the dot pattern is formed so as to overlap the normal image as shown
5 in FIG. 3.

A processing in the dot pattern forming unit 106 in this embodiment will hereinbelow be described with reference to FIGS. 5 and 6. Note that, while in the processing in this embodiment, a dot pattern as
10 shown in FIG. 7 is formed as the dot pattern, this example is merely an example, and hence another dot pattern may be formed in accordance with another method.

As shown in FIG. 5, the dot pattern forming
15 unit 106 is composed of four circuits composed of a counter 8A circuit 201, a counter 6 circuit 202, a counter 8B circuit 203, and an LUT 204.

As an example, it is assumed that the number, m , of dots of a minute dot area forming the dot pattern
20 in a main scan direction X is 8, and the number, n , of dots in a sub-scan direction Y is 6, and the number, k , of shift dots is 1. In addition, in this embodiment, it is assumed that the number of dots which the dot toner images formed within the dot area
25 have is only 1, and its position is expressed in the form of (main scan direction X , sub-scan direction Y) = (3, 0) within the dot area.

Hence, an operation of the dot pattern forming unit 106 shown in FIG. 6 will hereinbelow be described.

The counter 8A circuit 201 counts the position
5 in the main scan direction X by the number, m, of
counts = 8, and hence repeats counting from 0 to 7 as
one partition of the dot area in response to an image
clock signal as a clock input signal to divide the
additional image formation area in the main scan
10 direction X into dot areas.

Load of an initial value as the number of
counts for the position at the leading end of the dot
pattern area in the main scan direction becomes
possible. Then, a main scan top signal is made a
15 load signal with a value of an output signal of the
counter 8B circuit 203 as an initial value. Since an
initial value of the counter 8B circuit 203 is 0 in
this case, the counter 8A circuit 201 counts as 0 the
leading end portion of the dot pattern area in the
20 main scan direction to repeat counting from 0 to 7
until the laser beam reaches the trailing end of the
dot pattern area in the main scan direction.

The counter 6 circuit 202 is a counter for
counting up taking a main scan top signal as a clock
25 signal, and hence repeats counting from 0 to 5. That
is, whenever the counting in the main scan direction
by the counter 8A circuit 201 is ended one, the

counter 6 circuit 202 counts up by 1. That is, the counter 6 circuit 202 counts the position in the sub-scan direction by the number, n, of counts = 6.

The counter 8B circuit 203 is a counter for
5 counting an initial value when the shift is carried out. Then, whenever the counter 6 circuit 202 counts the position in the sub-scan direction from 0 to 5 and the count is returned back to 0 again, i.e., whenever an overflow occurs in the counter 6 circuit
10 202, the circuit 8B circuit 203 counts up. Then, upon input of the main scan top signal, the counter 8A circuit 202 is loaded with the count value. In other words, after the counter 8A circuit 201 repeatedly counts the position from one end of the
15 dot pattern to the other in the main scan direction by 6, the counter 8B circuit 203 counts up by 1. Then, the number of initial counts obtained when the counter 8A circuit 201 is loaded with the main scan top signal is incremented by 1. Then, if the count
20 initial value is 0, then the number of counts is changed to 1, and then the counting is executed from 1 to 2, 3, 4, ... in the main scan direction.

A count value of the counter 8A circuit 201 and a count value of the counter 6 circuit are both
25 inputted to the LUT 204. If a combination of the count value of the counter 8A circuit 201 and the count value of the counter 6 circuit agrees with a

value set in the LUT 204, then an output signal of the LUT 204 goes to "H" so that a minute dot toner image is formed. In this embodiment, the dot toner image is formed in a position, expressed in the form of $(X, Y) = (3, 0)$, where the counter 8A circuit 201 counts 3 and the counter 6 circuit 202 counts 0.

The dot pattern forming unit 106 is thus operated, with the result that the minute dot pattern is formed as shown in FIG. 7. Each quadrilateral shown in FIG. 7 is a pixel (dot), and the dot toner image of the dot pattern is formed in each pixel indicated by slant lines.

The counter 8A circuit 201 counts the position of the dot pattern in the main scan direction taking as an initial value the count value of the counter 8B circuit 203 obtained whenever the counter 6 circuit 202 counts the position in the sub-scan direction by 6. Hence, as the counting in the sub-scan direction is advanced, the position where the dot toner image is formed at the count of the counter 8A circuit 201 = 3 is shifted in the main scan direction by the number, k , of shift dots = 1.

Whenever six lines in the main scan direction are scanned, the main scan position of the dot toner image is shifted by the number, k , of shift dots = 1 in a direction opposite to the main scan direction. Hence, the main scan positions where the dot toner

images are respectively formed become uniform. As a result, the image forming apparatus is free from a problem such that longitudinal streak dirt occurs on the secondary transferring roller, the toner collects
5 in a specific position of the cleaning blade, or the dot toner image transferred onto the transferring material is conspicuous.

In this embodiment, the number, k , of shift dots is set to 1. However, in a case where a size, m ,
10 of the dot area in the main scan direction is 8 dots, even if such a value that a greatest common divisor between m such as 3, 5 or 7 and k becomes 1 may be adopted as the number, k , of shift dots, it is possible to unify the main scan positions where the
15 dot toner images are respectively formed.

As described above, since the dot pattern thus formed is formed over the whole sheet area shown in FIG. 3 so as to overlap the normal image, there is provided a state where the developer is already
20 present in the nip portion defined between the photosensitive drum 11d and the intermediate transferring belt 31 at a timing when the normal image arrives at the transferring portion Ta. As a result, it is possible to provide the image forming
25 apparatus which is capable of carrying out the stabler image formation and printing an image having high quality. With the image forming apparatus, even

when there is a difference in peripheral speed
between each of the photosensitive drums 11a to 11d
and the intermediate transferring belt 31, a
fluctuation in coefficient of friction depending on
5 presence or absence of the toner between each of the
photosensitive drums 11a to 11d and the intermediate
transferring belt 31 and a change in rotational speed
of each of the photosensitive drums 11a to 11d are
prevented, and generation of an image streak in the
10 leading end portion of the image due to the blurring
when images are exposed to the drums 11a to 11d is
avoided. Further, a level of a radiation noise does
not increase, and the longitudinal line streak dirt
does not occur on the secondary transferring roller
15 36.

Note that, in this embodiment, when the dot
pattern is traced in the sub-scan direction, the
position where the dot toner image is formed is
shifted in the main scan direction. Hence, the
20 oblique line-like dot pattern shown in FIG. 7 is
formed as the whole image. If such a pattern is
formed, then an image in which the dots are dotted in
a state of being fixed in the main scan direction is
difficult to be formed. However, the present
25 invention is not intended to be limited to such a
pattern. Hence, a suitable image may be selected as
the image which is formed in the form of the dot

pattern depending on a kind of normal image and other conditions. In such a case, the method including counting the number of positions in the main scan direction and in the sub-scan direction in the
5 counters, and the positions of the dot toner images in each dot area may be changed, or the dot area may not be partitioned in some cases.

However, in a case where the dot pattern and the normal image are formed so as to overlap each
10 other as described above, the dot toner image may be conspicuous in a white background portion of the normal image, or the dot pattern may appear to generate roughness in the normal image in some cases. The roughness especially remarkably appears when in
15 particular, the dot pattern of a half tone having low density is formed so as to overlap the set-solid image having high density.

Then, in order to solve such inconvenience, the present invention has a feature that the density of
20 the normal image based on the external information is judged every dot in the area where the dot pattern and the normal image are formed so as to overlap each other, and the output density in each dot is adjusted on the basis of the judgement results to thereby
25 suppress the conspicuousness and roughness.

In this embodiment, as described above with reference to FIG. 4, the density discriminating

circuit 104 determines whether or not the dot toner images should be formed in the dots in the dot pattern formation area, or determines the density of the dot toner images to be formed.

5 A processing in the density discriminating circuit 104 shown will hereinbelow be described with reference to a flow chart having Steps S1 to S5 of FIG. 1. In this embodiment, it is assumed that a density value A of an image density signal in each
10 dot is in the range of 256 gradations from 00h to FFh, and a density value B of an added predetermined pattern is C0h.

 The predetermined density B is set to density of which a dot pattern is not conspicuous so much
15 even when the dot pattern is formed in a white background portion of the normal image. The dot pattern becomes better as the density becomes lower in terms of conspicuousness. However, since the electrostatic latent image is shallower in the case
20 of low density, in a case as well where dots are formed with the same density, an amount of toner actually dotted disperses due to a difference among machines, and hence the expanded effects may not be obtained in such cases. Thus, in the case of a
25 machine construction capable of providing excellent dot rendering, the value equal to or larger than an intermediate value (40h) is selected as the density,

while in the case of a machine construction unable to provide excellent dot rendering, the value equal to or larger than 80h is used as the density.

In Step S1: The image density signal (a) and
5 the dot pattern signal (b) (refer to FIG. 4) are inputted to the density discriminating circuit 104 every input of an image clock signal.

In Step S2: It is judged in Step S1 whether or not a logical value of the dot pattern signal (b)
10 inputted to the density discriminating circuit 104 is 1. If it is judged that the logical value is 1, then the dot concerned is judged to be the dot with which the dot toner image is to be added.

In Step S3: If the judgement result in Step S2
15 is YES, then it is judged whether or not the normal image density value A based on the image density signal (a) is larger than the predetermined value B = C0h.

In Step S5: If it is judged in Step S3 that the
20 normal image density value A is equal to or smaller than the predetermined value B = C0h, the density concerned is lighter than the density set in the dot pattern, so that the density discriminating circuit 104 outputs a signal corresponding to C0h as the
25 predetermined density value B to the PWM circuit 107.

In Step S4: If the judgement result in Step S2 is NO, i.e., if a logical value of the dot pattern

signal (b) is 0, the dot concerned is not the dot with which the dot pattern is to be added, so that the density discriminating circuit 104 outputs a signal corresponding to the normal density value A from the image density signal (a) to the PWM circuit 107 as it is. In addition, in a case as well where it is judged in Step S3 that the normal image density value A is larger than the predetermined density value B = C0h, in order to make the image rendering excellent, the density discriminating unit outputs a signal corresponding to the normal density value A based on the image density signal (a) to the PWM circuit 107 as it is.

If as an example, the output density C is judged in accordance with the flow chart shown in FIG. 1 with respect to four kinds of combinations of the normal image density A and the input value b based on the dot pattern signal (b) which is composed of (80h, 0), (80h, 1), (E0h, 0), and (E0h, 1) to express such a combination in the form of (A, b) → the output density value C, the following results are obtained:

(80h, 0) → 80h
(80h, 1) → C0h
(E0h, 0) → E0h
(E0h, 1) → E0h

Thus, in the formation of the dot pattern, the dot toner image is added with C0h as the

predetermined density to a portion in which the density of the normal image of the dot portion in the dot pattern to which the dot toner image is added is lighter than the predetermined density C0h. On the other hand, when the density of that portion is darker than the predetermined density C0h, the image is formed with the normal image density while the density information based on the image signal is kept as it is. That is, when the density of the normal image is darker than the predetermined density, in this one dot, the developer of yellow is used on the photosensitive drum 11d so that its density agrees with the density of the normal image.

For that reason, the dot toner image is not formed in a portion having light density in the normal image in a state where the density of the dot toner image is darker than the predetermined density, and hence is hardly conspicuous even if the dot toner image is formed so as to overlap a white background portion of the normal image. Moreover, since the dot pattern having density lighter than that of the normal image is not formed so as to overlap a portion having dark density in the normal image, the dot pattern is not enhanced in the normal image, and hence no roughness or the like occurs in the image.

Second Embodiment

Next, a second embodiment will hereinbelow be

described. A difference from the first embodiment lies in a method including generating the PWM signal inputted to the laser unit 105. FIG. 8 is a block diagram showing a construction of this embodiment.

5 The image density signal (a) generated in the image processing unit 103, and the dot pattern signal (b) generated in the dot pattern forming unit 106 are directly inputted to the PWM circuit 107.

Two PWM tables are prepared within the PWM
10 circuit 107, and the dot pattern signal (b) inputted to the PWM circuit 107 is used to select between the two tables. That is, when a logical value of the dot pattern signal (b) is 0, a PWM table T0 is used, while when a logical value of the dot pattern signal
15 (b) is 1, a PWM table T1 is used.

The PWM tables T0 and T1 which are adopted in this embodiment are shown in FIGS. 9A and 9B, respectively.

As shown in FIG. 9A, the PWM table T0 is a
20 table for generation of a signal corresponding to a pulse width which increases in proportion to the level of the image density signal. Then, when the image density A based on the image density signal (a) is 00h, the pulse width becomes 0, while when the
25 density A of the normal image is FFh, full lighting data corresponding to the maximum pulse width is generated.

On the other hand, as shown in FIG. 9B, in accordance with the PWM table T1, when the density A of the normal image is equal to or lighter than that indicated by C0h, a signal having a constant pulse width corresponding to C0h of the PWM table T0 is generated, while the density A of the normal image is darker than that indicated by C0h, a signal having a pulse width which increases in proportion to the density A of the normal image is generated.

As a result, the pulse width signal similar to that in the circuit of the first embodiment is obtained. Thus, the dot toner image is formed with the predetermined density $B = C0h$ so as to overlap a portion in which the density indicated by the image density signal is lighter than the density indicated by the predetermined value B, while when the density indicated by the image density signal is darker than the density indicated by the predetermined value B, the dot toner image is formed using the image density signal directly. Hence, no conspicuousness, roughness or the like of the dot toner image occurs in the image.

Note that, in this embodiment, the dot dispersion image is formed over the whole area of the transferring material area. However, the dot dispersion image may not be formed over the whole area of the transferring material area, and hence may

be formed in a portion on an upstream side in the travel direction of the intermediate transferring belt with respect to the image formation area as well as in an area overlapping the normal image area
5 within the transferring material area. Thus, the present invention is applied to a portion of the dot toner image overlying the normal image.

As described above, in this embodiment, the present invention has been described with respect to
10 the color image forming apparatus which has such a construction as to have a plurality of photosensitive drums and which is adapted to form an image with a plurality of colors. However, the image forming apparatus is not limited to the above construction.
15 Hence, the present invention may also be applied to a single color image forming apparatus, or an image forming apparatus having one photosensitive drum.

For example, appearance of the image streak due to a change in frictional force is not limited to
20 only the operation for forming a color image. Thus, for example, in a case where an image with single color of black is formed using a color copying machine, or even in a monochrome copying machine, light and shade image streaks appear due to a change
25 in frictional force. Hence, there is a need to form dot toner images of black. In this case as well, the present invention is applied to realize the image

forming apparatus which is capable of preventing dot toner images from being conspicuous, and also capable of preventing image quality from being degraded due to roughness or the like.

5 In addition, the present invention may be applied to an image forming apparatus using no intermediate transferring body, e.g., a system as well, as shown in FIG. 12, for directly transferring a developer image from an image bearing body onto a
10 transferring material (recording material) with which a transferring material conveying body (transferring medium) or the like is loaded. In this example, a peripheral speed difference is provided in many cases between a travel speed of the transferring material
15 carrying body and a travel speed of the image bearing body.

 In FIG. 12, the same constituent elements as those of FIG. 10 are designated with the same reference numerals. In this image forming apparatus,
20 the recording material P accommodated in the cassette is fed by the sheet feeding roller 26 to be carried and conveyed by a conveying belt 100 which is stretched across a plurality of rollers. Images formed in the respective image forming units are
25 successively transferred onto the recording material P being carried and conveyed, and thereafter the fixing operation is carried out for the recording

material P by the fixing unit 40. The formation of
the dot image as described above in the first
embodiment is carried out in this image forming
apparatus as well, whereby the same effects can be
5 produced.

In addition, even with a construction in which
no peripheral speed difference is provided between
the image bearing body and the transferring movement
unit, a non-intentional speed difference may be
10 generated due to the decentering or the like of the
drive roller in some cases, so that the present
invention can be applied to such a construction.

Also, the scope of the present invention is not
intended to be limited to only the sizes, materials,
15 shapes, the relative positions and the like of the
constituent elements of the image forming apparatus
described above, as long as a specific description of
those factors is not especially made.